

TSP VFC

Total Suspended Particulate, Volumetric Flow Controlled



VFC TSP Ambient Air Sampler

The TE-5170V is a high volume ambient Total Suspended Particulate (TSP) air sampler featuring a volumetric flow controller (VFC) for accurate and consistent particulate sampling. The volumetric flow controller maintains a constant flow rate as the sampler operates to collect an accurate and representative sample. The system utilizes a stainless steel filter holder for use with standard 8"x 10" filter paper. The anodized aluminum shelter and robust electrical components allow the system to operate a continuous 24 hour sample.

ABOUT US: Tisch Environmental Inc. Tisch Environmental is the benchmark for high volume air sampling, particulate, metals, volatiles, and specialty monitoring equipment. Since the company's inception in 1953 as General Metal Works, our product line has expanded from the first high volume air sampler to include high-tech and custom samplers. Our clients are professionals from every sector of the regulatory and industrial markets.

For more information, contact us : Pacwill Environmental 905.563.9097 Toll-Free (Canada): 1-866-840-0014

- Meets EPA CFR, Appendix B to Part 50
- Total Suspended Particulate(TSP)
- **Volumetric Flow Controlled**
- 7-Day Mechanical Timer
- Elapsed Time Indicator
- Aluminum OutdoorShelter
- Brush Style Motor
- Dickson Chart Recorder, 24 Hour
- Stainless Steel Filter Holder
- **3** 44 CFM
- Made in USA



sales@pacwill.ca www.pacwill.ca



TSP VFC

VFC TSP Ambient Air Sampler

General System Specifications

Particulate Size:Total Suspended Particulate (TSP) EPA Designation: CFR 40 Part 50 Appendix B Flow Controller: Volumetric Flow Controller Motor Style:Brush Style Motor Assembly Pressure Recorder:Dickson Chart Recorder, 24 hour Timer:7 Day Mechanical Elapsed Time Indicator: Mechanical, Hours and Tenths Flow Range:44CFM, 1.24M³M Housing:Anodized Aluminum Fliter Holder:Stainless Steel, 8" x 10" 4" Recorder Charts: Box of 100 Filter Holder: 8" x 10" Stainless Steel with hold down frame Manometer: 30" Slack Tube Water Manometer

Applications

US EPA Reference Method Sampling, CFR Appendix J Part 50 Regulatory Compliance Institutional Studies Construction Sites Bridge and Water Tower Painting Sites Fence Line Monitoring Industrial Monitoring Landfill Monitoring Public Health Applications

Optional Equipment

Available Models

TE-5170V TSP VFC, 110 Volt 60 Hertz, 8 Amps TE-5170VX TSP VFC, 220 Volt 50 Hertz 4 Amps TE-5170VXZ TSP VFC, 220 Volts 60 Hertz, 4 Amps

Calibration Equipment

TE-5028 -Variable Flow Calibration Kit TE-HVC-V Xcalibrator HiVol Calibrator TE-3000 Filter Holder Cartridge TE-G653 8" x 10" Glass Fiber Filter Media TE-33392 Motor Brush Set (110volt) TE-33378 Motor Brush Set (220volt) TE-115923 Replacement Motor (110volt) TE-116111 Replacement Motor (220volt) TE-106 Recorder Charts TE-160 Recorder Pen Points TE-5018 Gasket 8" x 10"

Physical Specifications

Weight: 75lbs, Shelter
Shlpping Dimensions: 48"W x 20"L x 20" H, Shelter 19"W x 19"L x 20"H, Lid

Assembled Dimensions: 28"W x 28"L x 61"H

For more information, contact us : Pacwill Environmental 905.563.9097 Toll-Free (Canada): 1-866-840-0014

sales@pacwill.ca www.pacwill.ca

